

TEMP. (type K) TRANSMITTER

Model : TR-TMK1A4

ISO-9001, CE, IEC1010



Temp. probe
Optional



LUTRON ELECTRONIC

The Art of Measurement

Temperature (type K)

TRANSMITTER

Model : TR-TMK1A4-500C

Model : TR-TMK1A4-100C

Measure	TR-TMK1A4-500C	TR-TMK1A4-100C
Range	0 to 500 °C	0 to 100 °C
Output	4 - 20 mA	
	TR-TMK1A4-500C	TR-TMK1A4-100C
	0 °C = 4 mA 250 °C = 12 mA 500 °C = 20 mA	0 °C = 4 mA 50 °C = 12 mA 100 °C = 20 mA
External Adjustment	ZERO VR SPAN VR	
Power Supply	90 - 260 ACV 50 Hz/60 Hz	
Operation Temperature	0 - 50 °C 32 - 122 °F	
Operation Humidity	Less than 80 %RH	
Accessory Included	Type K temperature probe is optional.	
Optional Accessories	Type K temperature probe : TP-01 TP-02A TP-03 TP-04	
Mounting	Din rail or Wall	
Case	ABS plastic	
Others	Type K standard input socket	

* Appearance and specifications listed in this brochure are subject to change without notice.